

Baler

Many options and models available for the baler.

Roll baler: Hay silage innovator!



General specifications:

		Power round baler (RB models)	Power <u>CUT</u> round baler (CR models)
		Non-cutting type	Cutting type
1	Bale size	φ 90x 85cm / φ100x100cm / φ120~125x120cm	
2	Twine or net	Both options available	
3	Tire	Standard and big available	
4	Overall length (mm)	2,870 mm / 3,330 mm / 3,630 mm	
5	Overall width (mm)	1,780 mm / 2,130 mm / 2,300 mm	
6	Overall height (mm)	1,820 mm ~2,300mm	
7	Machine weight	1,150 kg ~ 1,255 kg	
8	Applicable tractor (kW [PS])	From 22.1 ~ 36.8 {30 ~ 50} to 36.8 ~ 73.5 {50 ~ 100}	From 25.7 ~ 44.1 {35 ~ 60} to 44.1~73.5 {60~100}
9	Connecting method with tractor	2P V-hitch	
10	Driving method	PTO Driving (500~540min-1)	
11	Working width (cm)	150 / 170 / 200 (cm)	
12	Working speed (km/h)	4~7 (depends on model)	3~7 (depends on model)
13	Working efficiency (min./10a)	8~17 (depends on model)	5~12 (depends on model)
14	Open and close of chamber	Depends on size and model	